


QPC6044

Absorptive High Isolation SP4T Switch 5 MHz to 6000 MHz


The QPC6044 is a Silicon on Insulator (SOI) single-pole, 4-throw (SP4T) switch, designed for use in cellular, 3G, LTE, and other high performance communications systems. It offers high isolation symmetric topology with excellent linearity and power handling capability. No blocking capacitors are necessary on the RF ports. The design is non-reflective such that the RFX ports are terminated into 50 Ω in the off state. QPC6044 is +1.8 V logic compatible, and incorporates a single pin to disable the internal Negative Voltage Generator (NVG) and supply a negative voltage from off-chip, if necessary.

Functional Block Diagram



Ordering Information

QPC6044SQ	Sample bag with 25 pieces
QPC6044SR	7" Reel with 100 pieces
QPC6044TR13	13" Reel with 2500 pieces
QPC6044PCK401	5 MHz to 6000 MHz PCBA with 5-piece sample bag



Package: QFN, 24-pin,
4.0 mm x 4.0 mm

Features

- 5 MHz to 6000 MHz Operation
- Symmetrical SP4T.
- Non-Reflective (RFX ports)
- Terminated All-Off State mode
- No Blocking Caps Necessary unless voltage is on RF Line
- High Isolation: 54 dB at 2 GHz
- High Input IP3: +61 dBm
- 2 kV ESD
- +1.8 V Logic Compatible

Applications

- Cellular, 3G, LTE Infrastructure
- WiBro, WiMAX, LTE
- High Performance Communications Systems
- Test Equipment

Absolute Maximum Ratings

Parameter	Rating	Units
Supply Voltage	+6	V
Control Voltage	-0.2 to +6	V
V _{SS} Supply	-6	V
Max RF Input Power, RFC/RFX non-terminated	+37.5	dBm
Max RF Input Power, RFX terminated	+29	dBm
Operating Temperature	-40 to +105	°C
Storage Temperature	-40 to +150	°C
Maximum Junction Temperature	+125	°C
ESD Rating	Human Body Model (HBM)	2000
	Charge Device Model (CDM)	1000
Moisture Sensitivity Level	2	—



Caution! ESD sensitive device.



RFMD Green: RoHS status based on EU Directive 2011/65/EU (at time of this document revision), halogen free per IEC 61249-2-21, < 1000 ppm each of antimony trioxide in polymeric materials and red phosphorus as a flame retardant, and <2% antimony in solder.

Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability. Specified typical performance or functional - operation of the device under Absolute Maximum Rating conditions is not implied.

Recommended Operating Conditions

Parameter	Specifications			Units
	Min	Typ	Max	
Operating Temperature Range	-40	+25	+105	°C
Operating Junction Temperature			+125	°C
Supply Voltage	+2.7	+5	+5.5	V
V _{SS} Supply (Applicable for off-chip negative supply, otherwise 0V (zero) for internal NVG operation)	-5.5	-5	-2.7	V

Electrical Specifications

Parameter	Specification			Units	Conditions
	Min	Typ	Max		
Test conditions unless otherwise noted: T _A = +25 °C, V _{CTRL} = 0/+5 V, V _{DD} = +3V to +5 V, 50 Ω system					
Operating Frequency Range	5		6000	MHz	
Insertion Loss		0.87		dB	450 MHz
		0.91		dB	900 MHz
		0.98	1.25	dB	2100 MHz
		1.00		dB	2600 MHz
		1.05		dB	4000 MHz
		1.20		dB	6000 MHz
Isolation (RFC – RFX)		66		dB	450 MHz
		61		dB	900 MHz
	50	54		dB	2100 MHz
		52		dB	2600 MHz
		48.5		dB	4000 MHz
		45.5		dB	6000 MHz

Electrical Specifications (contd.)

Parameter	Specification			Units	Conditions
	Min	Typ	Max		
Test conditions unless otherwise noted: T _A = +25 °C, V _{CTRL} = 0/+5 V, V _{DD} = +3V to +5 V, 50 Ω system					
Isolation (RFX – RFX)		62		dB	450 MHz
		57		dB	900 MHz
		50		dB	2100 MHz
		48		dB	2600 MHz
		45		dB	4000 MHz
		42		dB	6000 MHz
Return Loss (RFX On-State)		26		dB	450 MHz
		25		dB	900 MHz
		26		dB	2100 MHz
		27		dB	2600 MHz
		30		dB	4000 MHz
		20		dB	6000 MHz
Return Loss (RFX Off-State)		32		dB	450 MHz
		28		dB	900 MHz
		23		dB	2100 MHz
		22		dB	2600 MHz
		20		dB	4000 MHz
		15		dB	6000 MHz
Input IP2		TBD		dBm	
Input IP3	+55	+61		dBm	1 GHz, 17 dBm/tone, 1 MHz tone spacing
Input P1dB		+37		dBm	
Settling Time		1	4	μs	50% V _{CTRL} to optimum functionality
Start-up Time		5	25	μs	90% V _{DD} to full functionality
Switching Speed		150	500	ns	50 % control to 10/90 % RF
NVG Spur		-104		dBm	Internal NVG on.

Electrical Specifications – Power Supply

Parameter	Specification			Units	Conditions
	Min	Typ	Max		
Test conditions unless otherwise noted: T _A = +25 °C, V _{DD} = +3V to +5.0 V, Standard Application Circuit					
Supply Current (I _{DD})		100		μA	V _{DD} = +5 V
Control Current (V1, V2, V3)		2		μA	V _{CTRL} = +5 V
V _{SS} Current		100		μA	V _{SS} = −5 V, NVG is shut down.
Low Control Voltage (V1, V2, V3)	0		+0.63	V	+1.8 V Logic Compatible
High Control Voltage (V1, V2, V3)	+1.1		V _{DD}	V	+1.8 V Logic Compatible

Maximum Operating Power at High Temperature, CW, ≥ 50 MHz, 50 Ω System

Input	Power (dBm) at each port		Theta-J ($^{\circ}$ C/W)
	85 $^{\circ}$ C	105 $^{\circ}$ C	
RFC/ RFX – Active ¹	35.4	32.2	56
RFX – Terminated (1 path)	27.8	24.8	66
RFX – Terminated (2 adjacent paths)	26.7	23.7	85
RFX – Terminated (all paths)	26.6	23.6	86

Notes:

- For frequencies <50 MHz, maximum operating power at all temperatures should be at least 2 dB less than P1dB compression from plot.


Truth Table – 3 Pin Control

MODE	V1	V2	V3
Unsupported	0	0	0
RFC-RF1 active	1	0	0
RFC-RF2 active	0	1	0
RFC-RF3 active	1	1	0
RFC-RF4 active	0	0	1
All off	1	0	1
All off	0	1	1
All off	1	1	1







Truth Table – 2 Pin Control (V3 must be grounded)

MODE	V1	V2
RFC-RF1 active	1	0
RFC-RF2 active	0	1
RFC-RF3 active	1	1
RFC-RF4 active	0	0


QPC6044 Typical Performance



Typical Performance (continued)




Typical Performance (continued)



QPC6044


Evaluation Board Schematic and PCB – 5MHz to 6000 MHz Application Circuit



Evaluation Board Bill of Materials (BOM) - 5 MHz to 6000 MHz Application Circuit

Description	Reference Designator	Manufacturer	Manufacturer's P/N
Evaluation Board	—	Viasystems Technologies Corp.	QPC6064-410(B)
CAP, 100 pF, 5 %, 50 V, COG, 0402	C1-C5	Taiyo Yuden	RM UMK105CG101JV-F
CONN, SMA EL FLT VIPER, MAT-21-1038	J1 – J4, J6	Amphenol RF Asia Corp	901-10425
CONN, HDR, ST, PLRZD, 6-PIN	P1	AMP	640454-6
QPC6044	U1	RFMD / Qorvo	QPC6044


Pin Configuration and Description



Pin	Label	Description
1–4, 6, 7, 9, 10, 12, 13, 15, 21, 23, 24	GND	Connect to Low inductive Path to Ground
5	RF4	RF Port 4
8	RF3	RF Port 3
11	RF2	RF Port 2
14	RF1	RF Port 1
16	V _{DD}	Supply Voltage
17	V1	Control Pin
18	V2	Control Pin
19	V3	Control Pin
20	V _{SS} /GND	Negative Voltage Generator (NVG) control pin. Supply GND (Low inductive path to ground) to enable internal NVG or supply –2.7 V to –5 V to disable internal NVG. Once disabled, internal NVG cannot be enabled without cycling VDD.
22	RFC	RF common Port
Backside Pad	GND	Connect to Low inductive Path to Ground

QPC6044

Package Marking



PCB METAL LAND PATTERN

12x 2.130
PIN 1
4x 1.250
4x 0.750
4x 0.250
4x R0.14
12x 1.865
12x 1.865
(2.700)
0 (2.700)

PCB SOLDER MASK PATTERN

12x 2.180
PIN 1
4x 1.250
4x 0.750
4x 0.250
4x R0.21
12x 1.865
12x 1.865
(2.840)
0 (2.840)

PCB STENCIL PATTERN

12x 2.103
PIN 1
4x 1.250
4x 0.750
4x 0.250
R0.12
12x 1.865
12x 1.865
(2.430)
0 (2.430)

DETAIL A
PAD
SCALE:2X
12X THIS ROTATION
12X ROTATED 90°

DETAIL A
PAD
SCALE:2X
12X THIS ROTATION
12X ROTATED 90°

DETAIL A
PAD
SCALE:2X
12X THIS ROTATION
12X ROTATED 90°

Thermal vias for center slug should be incorporated into the PCB design. The number and size of thermal vias will depend on the application, the power dissipation, and the electrical requirements. Example of the number and size of vias can be found on the RFMD evaluation board layout.

QPC6044



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.rfmd.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

For information about the merger of RFMD and TriQuint as Qorvo:

Web: www.qorvo.com

Important Notice

The information contained herein is believed to be reliable. RFMD makes no warranties regarding the information contained herein. RFMD assumes no responsibility or liability whatsoever for any of the information contained herein. RFMD assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RFMD products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RFMD products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.