

Part Number: 1200980213

Product Description: PROFIBUS Straight D-Sub to Dual D-Sub, Straight To 90°, 22 AWG, PUR Cable, 1.0m (3.28') Length

Status: Active

**Engineering Number:** MP3G72PP4M010

Series Number: 120098

**Product Category:** Circular Industrial

Cordsets

#### **Documents & Resources**

#### **Drawings**

Drawing 1200980213\_sd.pdf

## **Product Environment Compliance**

#### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### **EU RoHS Certificate of Compliance**

#### **Part Details**

#### General

Status	Active
Statas	7 (66.7 6

Category	Circular Industrial Cordsets
Series	120098
Description	PROFIBUS Straight D-Sub to Dual D-Sub, Straight To 90°, 22 AWG, PUR Cable, 1.0m (3.28') Length
Comments	With Programming Port
IP Rating	IP40
Product Family	PROFIBUS Solutions
Product Name	PROFIBUS
Protocol	N/A
Region	America, Asia, Europe
Туре	Double Ended
UPC	78172504529

## Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

# Physical

Cable Diameter	8.00mm (.315")
Cable Length	1.0m (3.28')
Color - Cable Jacket	Violet
Connector End A	D-Sub (9-pin)
Connector End B	Dual D-Sub (9-pin)
Coupling Style	Threaded
Gender	Male-Male
Keyway	None
LED Indicator	No
Material - Cable Jacket	PUR
Material - Connector Body	PUR
Material - Contact	N/A
Material - Coupling Nut	Gray Anodized Aluminum
Material - Plating Mating	N/A
Orientation	90° to Straight
Poles	9
Temperature Range - Operating	0° to +60°C

Wire/Cable Type	Shielded-Twisted Pair
Wire Size (AWG)	22

This document was generated on Sep 17, 2024