

UL PICCOLO UL PC B 65 G



Sample photo

Order symbol: UL PC B 65 G
Product nbr: 8714303
Description: UL Enclosure, PC
Remarks: Grey cover

EAN: 6418074038814
EI. number:
Finland:
Electric No.: 8212031018
Denmark:
Electric No. Italy: 7201010U

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

Dimensions:		Length	Width	Height	Rating:
mm:		110	80	65	Ingress Protection (EN 60529): IP66/IP67
inch:		4.3	3.1	2.6	Impact Resistance (EN 62262): IK08
Materials:					Electrical insulation: Totally insulated
Material:		Polycarbonate			Halogen free (DIN/VDE 0472, Part 815): 1
Base colour:		RAL 7035 -light grey			UV resistance: UL 508
Cover screws material:		Polyamide			Flammability Rating: UL 746C 5"
Cover colour:		RAL 7035 -light grey			UL Type:
Cover screws colour:		Grey			Glow Wire Test (IEC 695-2-1) °C: 960
Gasket material:		Polyurethane			Certificates:
Temperatures:					Underwriters Laboratories
Temperature °C (short term):		-40 ... 120 °C			SGS Fimko
Temperature °C (continuous):		-40 ... 80 °C			UL Canada
Temperature °F (short term):		-40 ... 250 °F			Gost R
Temperature °F (continuous):		-40 ... 175 °F			

PICCOLO 110x80x65-85

