

A

B

C

D

E

F

A

B



C

D


E

Die deutsche Version dieser Zeichnung dient nur zur Erleichterung der Handhabung bei Abweichungen von den englischen Original gilt als verbindlich. Bei Abweichungen von den englischen Original gilt das englische Original.
The german version of this drawing has been offered for convenience only and may deviate from the english original.
In case of any deviation the English version shall prevail.



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz.
Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Geschmucksmusterung vorbehalten.
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.




Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT




ohne Ansaughauke -without hood



Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 280 Stück
packaging unit: 280 pcs



Abspulrichtung - reel off direction




Anforderungsstufe 1
performance level 1

Kontaktbereich vergoldet
mating area gold plating

Anschlussbereich verzinkt 4-6 µm
terminal area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
coplanarity area of termination ≤ 0,1 mm

BA 8-03 - Standard Bauhöhe
type 8-03 - Standard Assembly Height

Dimension no.				Tolerances Dim. for Information ISO 8015		 All Dimensions in mm		Scale 3:1		Material	
Customer drawing: THIS DRAWING IS A CONTROLLED DOCUMENT.				Subject to modification without prior notice. Drawing will not be updated.				ERNI-Messerl. SMC-Q 26-SMD-BA8-03 Male SMC-Q 26-SMD-type8-03			
f				01.10.2019				©- 244855-E SMCQ			
Index				Date							
								I A3			