# 3M<sup>™</sup> Mini Serial Attached SCSI (miniSAS) Cable Assembly

Internal, Signal, Straight Termination

8N36 Series



- 3 Gbps per channel data rate
- 36 Conductor signal assembly
- Multiple lengths available
- Metal latch designed to ensure retention
- Two levels of EMLB for hot plugging
- 30 AWG Twin Axial Cable
- Universal key
- Tested to SAS Specification, SAS-1.1
- See Regulatory Information Appendix (RIA) for chemical compliance information

Date Modified: July 3, 2007

TS-2209-C Sheet 1 of 3

## **Physical**

Backshell

Material: High Temperature Thermoplastic

Flammability: UL 94V-0 Color: Black

**Paddle-card** FR4 Flammability: UL 94V-0

**Plating** 

Underplating:  $50 \mu$ " min. [  $1.27 \mu$ m ] Nickel Wiping Area:  $30 \mu$ " min. [  $0.76 \mu$ m ] Gold

Cable

Wire Size

Conductor: 30 AWG Solid Tin Plated Solid Conductor Drain Wire: 30 AWG Solid Tin Plated Solid Conductor

Dielectric: Foam Polyethylene Shield: Mylar 100% Coverrage

Jacket: Non-PVC

Jacket Braiding

Material: Nylon Braid

### **Electrical**

Current Rating: Per Contact: 0.5 AInsulation Resistance:  $10^3 \text{ M}\Omega \text{ min.}$ 


Withstanding Voltage: 300 V<sub>DC</sub> min. for 1 minute

#### **Environmental**

Operating Temperature: -20°C to +80°C

UL File No.: E86982

Internal, Signal, Straight Termination



P1		P2		
A1	GND	B1	GND	
A2	Rx 0+	B2	Tx 0+	
А3	Rx 0-	В3	Tx 0-	
A4	GND	B4	GND	
A5	Rx 1+	B5	Tx 1+	
A6	Rx 1-	B6	Tx 1-	
A7	GND	B7	GND	
A8	SIDEBAND 7	SIDEBAND 7 B8 S		
A9	SIDEBAND 3	B9	SIDEBAND 3	
A10	SIDEBAND 4	B10	SIDEBAND 4	
A11	SIDEBAND 5	B11	SIDEBAND 5	
A12	GND	B12	GND	
A13	Rx 2+	B13 Tx 2		
A14	Rx 2-	B14	Tx 2-	
A15	GND	GND B15		
A16	Rx 3+	B16	Tx 3+	
A17	Rx 3-	B17	Tx 3-	
A18	GND	B18 GND		

P1		P2		
B1	GND	A1	GND	
B2	Tx 0+	A2	Rx 0+	
В3	Tx 0-	A3	Rx 0-	
B4	GND	A4	GND	
B5	Tx 1+	A5	Rx 1+	
B6	Tx 1-	A6	Rx 1-	
B7	GND	A7	GND	
B8	SIDEBAND 0	A8	SIDEBAND 0	
В9	SIDEBAND 1	A9	SIDEBAND 1	
B10	SIDEBAND 2	A10	SIDEBAND 2	
B11	SIDEBAND 6	A11	SIDEBAND 6	
B12	GND	A12	GND	
B13	Tx 2+	A13	Rx 2+	
B14	Tx 2-	A14	Rx 2-	
B15	GND	GND A15 GN		
B16	Tx 3+	A16	Rx 3+	
B17	Tx 3-	A17	Rx 3-	
B18	GND	A18	GND	

#### Pinout 1

#### **Backplane-to-Controller**

	P1	P2		
A1	GND	B1	GND	
A2	Rx 0+	B2	Tx 0+	
A3	Rx 0-	В3	Tx 0-	
A4	GND	B4	GND	
A5	Rx 1+	B5	Tx 1+	
A6	Rx 1-	B6	Tx 1-	
A7	GND	B7	GND	
A8	SIDEBAND 7	B11	SIDEBAND 5	
A9	SIDEBAND 3	B10	SIDEBAND 4	
A10	SIDEBAND 4	B9	SIDEBAND 3	
A11	SIDEBAND 5	B8	SIDEBAND 7	
A12	GND	B12 GNI		
A13	Rx 2+	B13	Tx 2+	
A14	Rx 2-	B14	Tx 2-	
A15	GND	B15	GND	
A16	Rx 3+	B16	Tx 3+	
A17	Rx 3-	B17	Tx 3-	
A18	GND	B18	GND	

	P1	P2			
B1	GND	A1	GND		
B2	Tx 0+	A2	Rx 0+		
B3	Tx 0-	A3	Rx 0-		
B4	GND	A4	GND		
B5	Tx 1+	A5	Rx 1+		
B6	Tx 1-	A6	Rx 1-		
B7	GND	A7	GND		
B8	SIDEBAND 0	A11	SIDEBAND 6		
B9	SIDEBAND 1	A10	SIDEBAND 2		
B10	SIDEBAND 2	A9	SIDEBAND 1		
B11	SIDEBAND 6	SIDEBAND 6 A8 SID			
B12	GND	A12	GND		
B13	Tx 2+	A13	Rx 2+		
B14	Tx 2-	A14	Rx 2-		
B15	GND	A15	GND		
B16	Tx 3+	A16	Rx 3+		
B17	Tx 3-	A17	Rx 3-		
B18	GND	A18	GND		

#### Pinout 2

#### **Controller-to-Controller**

TS-2209-C Sheet 3 of 4

# 3M<sup>™</sup> Mini Serial Attached SCSI (miniSAS) Cable Assembly

Internal, Signal, Straight Termination

03.70	$\sim$ .
XN36	Series
01100	

	P1		P2
A1	GND	B1	GND
A2	Rx 0+	B2	Tx 0+
A3	Rx 0-	В3	Tx 0-
A4	GND	B4	GND
A5	Rx 1+	B5	Tx 1+
A6	Rx 1-	B6	Tx 1-
A7	GND	B7	GND
A12	GND	B12	GND
A13	Rx 2+	B13	Tx 2+
A14	Rx 2-	B14	Tx 2-
A15	GND	B15	GND
A16	Rx 3+	B16	Tx 3+
A17	Rx 3-	B17	Tx 3-
A18	GND	B18	GND

	P1		P2
B1	GND	A1	GND
B2	Tx 0+	A2	Rx 0+
B3	Tx 0-	A3	Rx 0-
B4	GND	A4	GND
B5	Tx 1+	A5	Rx 1+
B6	Tx 1-	Tx 1- A6	
B7	GND	A7	GND
B12	GND	A12	GND
B13	Tx 2+	A13	Rx 2+
B14	Tx 2-	A14	Rx 2-
B15	GND	A15 GND	
B16	Tx 3+	A16	Rx 3+
B17	Tx 3-	A17	Rx 3-
B18	GND	A18 GND	

#### Pinout 3

Backplane-to-Controller (no sidebands)

## **Ordering Information**

8N36 - AAXX05 - X.XX (RIA E1 & C1 Apply)

\* If other lengths are desired, contact your local 3M sales representative.

\*\* If keying other than Universal is desired, contact your local 3M sales representative.

TS-2209-C Sheet 4 of 4

# **Regulatory Information Appendix**

## 3M Electronic Solutions Division/Interconnect

## **EUROPE**

# **Appendix E1: European Union RoHS**

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

#### This product is RoHS Compliant 2005/95/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

# Appendix E2: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

This product contains lead in the compliant pin area in excess of the maximum concentration value allowed but is compliant by exemption under EU Commission Decision 2005/747/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

# **Appendix E3: European Union RoHS**

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment as amended by Commission Decision 2005/618/EC.

This product contains lead in the solder tail area in excess of the maximum concentration value allowed.

Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

# **Appendix E4: European Union RoHS**

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

This product contains decaBDE in the insulating material in excess of the maximum concentration value allowed but is compliant by exemption under EU Commission Decision 2005/17/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

# CHINA Appendix C1: China RoHS

Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part **does not** contain any of the following substances in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

# Appendix C2: China RoHS



Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part **does** contain a substance, as detailed in the chart below, in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

The numerical reference in the symbol above should not be construed as a representation regarding the product's life or an extension of a product warranty. The product warranty is stated below. In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the product Warranty stated below.

产品中有毒有害物质或元素的名称及含量 Name and Content of Hazardous Substances or Elements

部件名称	有毒有害物质或元素 (Hazardous Substances or Elements)					
(Part or Component Name)	铅(Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
端子镀层(contact plating)	×	0	0	0	0	0

O: 表示该有毒有害物质在该部件所有均质材料中的含量均在SJ/T11363-2006 标准规定的限量要求以下。(Indicates that this hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in SJ/T11363-2006.)

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



3M Electronics Interconnect Products 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3m.com/interconnects

<sup>×:</sup>表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006 标准规定的限量要求。(Indicates that this hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement in SJ/T11363-2006.)

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## 3M:

<u>8N36-AA0105-0.25</u> <u>8N36-AA0105-0.50</u> <u>8N36-AA0105-1.00</u> <u>8N36-AA0205-0.25</u> <u>8N36-AA0205-0.50</u> <u>8N36-AA0205-0.50</u> <u>8N36-AA0205-1.00</u> <u>8N36-AA0305-0.25</u> <u>8N36-AA0305-1.00</u>