




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.03 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	FLK

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Extraction Force	7 – 100 Newton
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Compatible Insulation Diameter Range	2.2 – 3.3 mm[.086 – .13 in]
Wire Size	.51 – 1.03 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	2000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part






numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 926291-1 PL 250 HOUSING FLAG PA 6.6 BLACK	 TE Part # 2150401-1 OCEAN_2.0_Applicator-E-100F140F-SEM	 TE Part # 2150401-2 OCEAN_2.0_Applicator-E-100F140F-SEA	 TE Part # 2150908-1 OCEAN-2.0-APPLICATOR-E-100F120OV-SEM
 TE Part # 2150908-2 OCEAN-2.0-APPLICATOR-E-100F120OV-SEA	 TE Part # 680436-1 HDM 9EMPO100F120F T&G	 TE Part # 7-2150401-7 OCEAN_2.0_SPARE_PART_KIT-100F140F	 TE Part # 7-2150908-7 OCEAN_2.0_SPARE_PART_KIT-100F120OV

Also in the Series | Positive Lock 250

 Automotive Terminals(1)	 Crimp Terminal Housings(190)	 Insertion & Extraction Tools(3)	 Insulation Boots & Sleeves(4)
 Quick Disconnects(185)			


Customers Also Bought



TE Part #316371-1
MULTILOCK, CONNECTOR HOUSING



TE Part #175193-1
187 PL EX FLAG REC. 22-16AWG PTBR




TE Part #929985-1
RECEPTACLE CONTACT 1,5MM DIA



TE Part #D58196-000
FL2500-NO.2-19-0-50MM



TE Part #2098067-2
Plug Assembly, Hybrid, BCM, IP2, B Key



TE Part #1-1924337-3
Shield Assy, 54 POSN, 0.64mm, 20 DEG BLK



TE Part #2098380-2
20 POS HYBRID UNSEALED CAP KY-B STD CLIP



TE Part #881762-1
3 WAY JPT ASS'Y



TE Part #85069-2
250 P.LOCK REC

Documents

Product Drawings

PL 250 FLAG REC 0.5-1.5 MM2 0.4X.44 PTP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_926820-4_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_926820-4_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_926820-4_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Positive Lock Receptacles

English

1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English