


AMP | Superseal Pro TE Internal #: 2345390-2 Plug, Wire-to-Wire, 3 Position, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Superseal Pro

#### View on TE.com >

Connectors > Automotive Connectors > Automotive Housings



Connector System: Wire-to-Wire

Number of Positions: 3

Connector & Housing Type: Plug

Centerline (Pitch): 5 mm [.197 in ]

Sealable: Yes

### Features

**E T E Connectivity** 

### Product Type Features

Mixed & Hybrid Connector	No	
Connector Shape	Rectangular	
Connector System	Wire-to-Wire	
Connector & Housing Type	Plug	
Sealable	Yes	
Connector & Contact Terminates To	Wire & Cable	
Primary Locking Feature	Integrated in Housing	
Configuration Features		
Number of Positions	3	
Number of Rows	1	
Electrical Characteristics		
Operating Voltage	50 VDC	
Body Features		
Primary Product Color	Black	

Plug, Wire-to-Wire, 3 Position, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Superseal Pro



Connector & Keying Code	II	
Contact Features		
Contact Size	2.8mm	
Contact Type	Receptacle	
Mating Tab Width	2.8 mm[.11 in]	
Contact Current Rating (Max)	30 A	
Mechanical Attachment		
Strain Relief	Without	
Mating Alignment Type	Keyed	
Mating Alignment	With	
Connector Mounting Type	Cable Mount (Free-Hanging)	
Housing Features		
Housing Material	PA 6 GF	
Centerline (Pitch)	5 mm[.197 in]	
Usage Conditions		
Operating Temperature (Max)	120 °C[248 °F]	
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]	

## Operation/Application

Circuit Application	Power
Packaging Features	
Packaging Quantity	600
Packaging Method	Box
Other	
Connector Position Assurance Capable	Yes
<b>Product Compliance</b> For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)

Plug, Wire-to-Wire, 3 Position, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Superseal Pro



Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Not reviewed for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




## Also in the Series | Superseal Pro

Automotive Connector Caps & Covers (3)	Automotive Housings(91)	Connector Backshells(13)	Connector Caps & Covers(1)

Plug, Wire-to-Wire, 3 Position, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Superseal Pro





## Customers Also Bought



MT-II/JPT SLD 36P CAP HSG	2 POS. PLUG ASSY, KEY B, GRAY	SEALING PLUG CONTACT DUMMY	2.5mm SOCKET HSG ASSEMBLY
		(MQS)	(GREEN 4POS)

### Documents

Product Drawings

### 3POS, AMP MCP 2.8, REC HSG ASSY, SLD, COD 2

English

### CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2345390-2\_B.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2345390-2\_B.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2345390-2\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**C** For support call+1 800 522 6752

Plug, Wire-to-Wire, 3 Position, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Superseal Pro



Product Specifications Product Specification

English