



Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 800 Stück
packaging unit: 800 pcs





Abspulrichtung - reel off direction



Leiterplatten-Layout Vorschlag
PCB-Layout Proposal



RoHS: 6/6
MSL: 1

Koplanarität der Anschlüsse ≤ 01 mm
coplanarity area of termination ≤ 0,1 mm

zweireihig, mit Zapfen

2 row, with pegs

Dimension no.	Tolerances Dim. for Information ISO 8015	All Dimensions in mm	Scale 5:1 Material
Customer drawing: THIS DRAWING IS A CONTROLLED DOCUMENT.	Subject to modification without prior notice. Drawing will not be updated.		ERNI-MicroStac Steckverb., 50 polig MicroStac Conn., 50 contacts
		TE Connectivity	C-114713-E — I
Index: 1 — Date: 12.11.2020			Class: MICROS — A3

Die deutsche Version dieser Zeichnung dient nur zur Erleichterung der Handhabung. Bei Abweichungen von den englischen Original gilt das englische Original.
The german version of this drawing has been offered for convenience only and may deviate from the english original.
In case of any deviation the English version shall prevail.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz.
Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten.
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.