



TECHNICAL

AGENCY APPROVAL: cULus
 RATED SUPPLY VOLTAGE: 120 VAC
 RATED CURRENT: UP TO 20 AMPS
 RESET TYPE: MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 5mA +/- 1mA
 OVERLOAD CURRENT: 120 AMPS, 50% INDUCTIVE
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS
 ENCLOSURE: TYPE 4X, IP69, IP69K

MATERIAL NO.	ENGINEERING NO.	POWER-UP
1301530136	20052-Y-2M	MANUAL

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
	DIMENSION UNITS	SCALE	CURRENT REV DESC: SALE DRAWING RELEASED.
$\nabla_A = 0$	INCH	NTS	EC NO: 669157 DRWN: VBASUTHKARP 2021/07/30 CHK'D: DNGUYEN62 2022/12/06 APPR: WLEUNG 2022/12/13
$\nabla_E = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)		
$\nabla_P = 0$	ANGULAR TOL	± °	INITIAL REVISION:
DIVISIONAL SYMBOLS	4 PLACES	±	DRWN: A.L 2007/01/24
	3 PLACES	±	APPR: WLEUNG 2022/12/13
	2 PLACES	±	
1 PLACE	±		DOCUMENT NUMBER
0 PLACES	±		1301530136
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING
			C-SIZE
		SERIES	130153
		MATERIAL NUMBER	SEE TABLE
		CUSTOMER	GENERAL MARKET
		DOC TYPE	PSD
		DOC PART	000
		REVISION	A
		SHEET NUMBER	1 OF 1



IN-LINE GFCI MANUAL RESET
20A 120 VAC 60HZ 2400W 26W47/27W47 & 32-5270

PRODUCT CUSTOMER DRAWING