




POLES	MATERIAL NO.	ENG. NO.	AMPS	LENGTH
3	1300640065	CC3030A48M020	32	2M +89-0MM (6'7"+3.50-0)
4	1300640187	CC4030A48M020	32	2M +89-0MM (6'7"+3.50-0)
4	1300640245	CC4030A48M100	32	10M +318-0MM (32'10" +12.5"-0")

C



WIRING DIAGRAM
3 POLE
1>--->1
2>--->2
3>--->3

WIRING DIAGRAM
4 POLE
1>--->1
2>--->2
3>--->3
4>--->4

SPECS:
OVERMOLD: GRAY PVC
INSERT: BLACK PVC
COUPLING NUT: ANODIZED ALUMINUM
CABLE: #10AWG GRAY PVC
DUAL RATED UL TC/OPEN WIRING & STOOW
ELECTRICAL: 600V AC/DC

ADDED PART NUMBER	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRAWN BY	DATE	TITLE	SCALE	DESIGN UNITS	PROJECTION		
	mm	INCH								
EC NO: IPG2016-1155	4 PLACES	±---	±---	B. RUPERT	01/12/10	QUICK CHANGE FEMALE/MALE STRAIGHT 3 & 4 POLE AS PORTABLES	1:2	INCH		
DRAWN BY:GUSTAFSON	3 PLACES	±---	±.005	CHEKED BY	DATE					
CHKD: M.ZELINSKI	2 PLACES	±---	±.010	B. WOODMAN	01/12/10					
APPR: B.WOODMAN	1 PLACE	±---	±.020	APPROVED BY	DATE					
REV: C	ANGULAR $\pm 1/2^\circ$		JFMURPHY	2010/01/15	moolex	MOLEX INCORPORATED				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		SEE CHART	SD-130064-065	SHEET NO. 1 OF 1				
SIZE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex](#):

[1300640078](#)