

product type designation

product description

PROFIBUS Plastic Fiber Optic standard cable

Fiber-optic cable with polyoptical fiber, preferred length, preassembled
 PROFIBUS Plastic Fiber Optic, Standard cable with 4 BFOC connectors,
 Length 80 m



suitability for use	Cable for indoor applications
version of the assembled FO cable	Assembled with four BFOC connectors
cable designation	I-V4Y(ZN)Y 2P 980/1000
wire length	80 m
optical data	
attenuation factor per length	
• at 650 nm / maximum	160 dB/km
• at 660 nm / maximum	230 dB/km
bandwidth length product	
• at 650 nm	1 GHz·m
mechanical data	
number of fibers / per FOC core	1
number of FO cores / per FOC cable	2
version of the FO conductor fiber	Step index fiber 980/1000 μm
outer diameter	
• of the optical fibers	980 μm
• of the optical fiber sheath	1000 μm
• of the FOC core sheath	2.2 mm
symmetrical deviation / of the outer diameter of the FOC core sheath	0.1 mm
outer diameter / of the cable	7.8 mm
symmetrical deviation / of the outer diameter of the line	0.3 mm
material	
• of the fiber-optic cable core	Polymethylmethacrylate (PMMA)
• of the optical fiber sheath	Fluoridated special polymer
• of the FOC core sheath	PA
• of the fiber-optic cable sheath	PVC
• of the strain relief	Kevlar fibers
color	
• of the FOC core sheath	orange/black
• of cable sheath	Violet
bending radius	
• with single bend / minimum permissible	100 mm
• with multiple bends / minimum permissible	150 mm
tensile load	
• during installation / short-term	100 N

<ul style="list-style-type: none"> during operation / maximum 	100 N
short-term shear force per length	100 N/cm
weight per length	65 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport during installation 	-30 ... +70 °C -30 ... +70 °C -30 ... +70 °C 50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2
chemical resistance	
<ul style="list-style-type: none"> to mineral oil to grease 	conditional resistance conditional resistance
radiological resistance / to UV radiation	not resistant
protection class IP	IP20
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> halogen-free silicon-free 	No Yes
product component / rodent protection	No
wire length	
<ul style="list-style-type: none"> for POF FOC / with PROFIBUS / maximum 	80 m
standards, specifications, approvals	
certificate of suitability	UL approval: cULus OFN FT1 (NEC Article 770, UL 1651) / CSA approval: OFN (CSA-Standard C22.2 No232)
<ul style="list-style-type: none"> RoHS conformity 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAX-Download-Manager to website: Industry Online Support 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified: 12/16/2020 