




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NO.	WEIGHT (APPROX.)
DP125E88TGY	1.25 lb (567 g)

- NOTES:
- SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AS WELL AS OPTIONAL ICONS.
  - MATERIAL: STEEL/BLACK POWDER COAT PANEL HOUSING; THERMOPLASTIC RESIN RJ45 MODULE; THERMOPLASTIC RESIN UL94V-0 PUNCHDOWN BLOCKS; THERMOPLASTIC RESIN UL94V-0 BEZEL ASSEMBLY; THERMOPLASTIC RESIN RETENTION CAP; THERMOPLASTIC RESIN UL94V-0 12 PORT PATCH PANEL WITH TWO 6 POSITION BEZELS ASSEMBLIES, 8 WIRES PER JACK ASSEMBLY.
  - THE PATCH PANEL IS DESIGNED TO SNAP INTO A STANDARD 589D WALL MOUNT BRACKET. DIMENSIONS IN PARENTHESES ARE IN METRIC.
  - USE 110 STYLE TERMINATION TOOL FOR PUNCH DOWN.
  - RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.



RETENTION CAP SNAPS ONTO CONNECTOR  
ONE CAP PER CONNECTOR



MODEL FILENAME	MO208BAG_12_PORT_03	SIZE	A
DRAWING FILENAME	MO2479ML_DC325_00A.PRT		
TITLE	DP5e 12 PORT PATCH PANEL CUSTOMER DRAWING		

		<b>PANDUIT</b> <sup>TM</sup> TINLEY PARK, IL 60477	
I.P.T. NUMBER PRODUCT SPEC WORK INSTRUCTION SCALE .25:1		PART NO. DP125E88TGY	
ALL DIMENSIONS ARE GIVEN IN INCHES. DIMENSIONAL TOLERANCES ARE: (1.X) ± .03 (1.XXX) ± .005 (1.XX) ± .01 ANGLES ± 1° REVIEW DRAWING NUMBERS		DRAWING NO. 02479 - 325	
THIRD ANGLE PROJECTION DRAWN BY NER	DATE 3-22-06	ECN 02479-325	OTH
REV R	DATE 3-22-06	BY NER	DESCRIPTION RELEASED TO PRODUCTION
REV R	DATE 3-22-06	BY NER	DESCRIPTION RELEASED TO PRODUCTION
REV R	DATE 3-22-06	BY NER	DESCRIPTION RELEASED TO PRODUCTION

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Panduit:](#)

[DP125E88TGY](#)