



Ordering Information:

A1501HE-2xXP - *** - ***
1 2 3

1.Part NO.

2.Material:

(Blank): Nylon 66,UL94V-0

PBT:PBT,UL94V-0

3.Material:

(Blank): White BL: Blue

IV: Ivory MG: Moss Green

TR: Tomato Red DPK: Dark Pink

SPECIFICATIONS:

Current Rating: 2A AC,DC (AWG #24)

Voltage Rating: 100V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 30mΩ Max.

Insulation Resistance: 500MΩ Min.

Withstanding Voltage: 500V AC/minute

Housing Material: Nylon 66,UL94V-0

Ordering Information & Dimensions

Part NO.	Dimensions(mm)			
	A	B	C	D
A1501HE-2x5P	6.00	11.20	7.50	9.30
A1501HE-2x6P	7.50	12.70	9.00	10.80
A1501HE-2x7P	9.00	14.20	10.50	12.30
A1501HE-2x8P	10.50	15.70	12.00	13.80
A1501HE-2x9P	12.00	17.20	13.50	15.30
A1501HE-2x10P	13.50	18.70	15.00	16.80
A1501HE-2x11P	15.00	20.20	16.50	18.30
A1501HE-2x12P	16.50	21.70	18.00	19.80
A1501HE-2x13P	18.00	23.20	19.50	21.30
A1501HE-2x14P	19.50	24.70	21.00	22.80
A1501HE-2x15P	21.00	26.20	22.50	24.30
A1501HE-2x16P	22.50	27.70	24.00	25.80
A1501HE-2x17P	24.00	29.20	25.50	27.30
A1501HE-2x18P	25.50	30.70	27.00	28.80
A1501HE-2x19P	27.00	32.20	28.50	30.30
A1501HE-2x20P	28.50	33.70	30.00	31.80

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE	
mm	4:1	1 of 1	1.50mm PITCH HOUSING	
DRWN	CHK'D	APPR	DRAWING NO.	
Chengbiao Ye	Djankui Wan	Jack Yin	A1501HE-2xXP	
General Tolerances		THIRD ANGLE PROJECTION	REV	
x.x±0.25			A3	
x.xx±0.20				
x.xxx±0.15				
ANGLES ±1°				

REV	DESCRIPTION	DATE
A3	CHANGE THE DRAWING	2025.05.12
A2	MODIFY DRAWING	2021.12.24
A1	MODIFY DRAWING	2021.10.26
A0	NEW RELEASE	2021.08.27