



SPECIFICATIONS:

1. ELECTRICAL CHARACTERISTICS:
 - 1-1. CONTACT RESISTANCE: 30mΩ MAX.
 - 1-2. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR ONE MINUTE.
 - 1-3. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
2. MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE :0.5-2.0KgF(REF.)
 - 2-2. WITHDRAWAL FORCE :0.8-2.0KgF(REF.)
3. LIFE TEST: 10,000 CYCLES.
4. TO CONFORM TO THE KRCDNN HAZARDOUS SUBSTANCE FREE SPEC.

| | | | | | | | | |
|-----------|------------------------|-------------------|--|------------------|---|--|-------------|-----|
| | | | GENERAL TOLERANCE | 制图 DRAWING | 深圳市华灿天禄电子有限公司 ShenzhenhuaciantianluELECTRONICS CO.,LTD | | | |
| | | | DIM TOL | 审核 CHECK | 产品名称 TITLE | TYPE C F 16P TOP MOUNT (L:7.35) WITH POST (单排 板上 带柱 四脚插板 绿胶芯) | 版本 REV. | A |
| 1 | 初版发行 | | X.X ±0.30 | 批准 APPROVAL | 产品料号 PART NO. | HC-TYPE-C-16P-01A-G | 单位 UNITS | mm |
| 序号 No. | 变更内容 MODIFY CONTENT | 日期 MODIFY DATE | X.XX ±0.20 X.XXX ±0.10 Angle ±3.0° | 投影 Projection | 材料 MATERIAL | | 页次 SHEET | 1/3 |