



SIPLUS DP PROFIBUS connector M R + PG 90° Cable outlet -25...+70°C
with conformal coating based on 6ES7972-0BB12-0XA0

mechanical data	
locking mechanism design	Screwed joint
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
• with condensation / maximum	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
• conformity acc. to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
• conformity acc. to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
• conformity acc. to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
environmental category / acc. to IEC 60721 / note	* The supplied plug covers must remain in place over the unused interfaces during operation!
coating / for equipped printed circuit board / acc. to EN 61086	Yes; Class 2 for high reliability
type of coating	
• protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test / of the coating / acc. to MIL-I-46058C	Yes; Discoloration of coating possible during service life
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal coating, Class A

last modified:

12/18/2020 