

Part Number: 50375043 Product Description: 2.50mm Pitch, Mini-SPOX Receptacle Crimp Housing, Single Row,

Friction Lock, 4 Circuits, Natural

Series Number: 5264 Status: Active

Product Category: Connector Housings Engineering Number: 5264-04

#### **Documents & Resources**

#### **Drawings**

Drawing 050375043\_sd.pdf

### 3D Models and Design Files

2D Drawing DXF 050375043.dxf

2D Drawing DXF (PDF) 050375043.pdf

3D Model 050375043\_stp.zip

### **Specifications**

Packaging Specification SPK-5264-001-001.pdf Product Specification 52641001-PS-000.pdf Product Specification PS-5264-001-001.pdf

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <b>©</b>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                     |
| REACH SVHC         | Not Contained per D(2024)4144-DC<br>(27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                          |

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

## General

| Status         | Active  |
|----------------|---|
| Category       | Connector Housings  |
| Series         | 5264  |
| Description    | 2.50mm Pitch, Mini-SPOX<br>Receptacle Crimp Housing, Single<br>Row, Friction Lock, 4 Circuits,<br>Natural |
| Application    | Signal, Wire-to-Board   |
| Product Family | Mini-SPOX Wire-to-Board<br>Connector System   |
| Product Name   | Mini-SPOX   |
| UPC            | 800753578364  |

# Agency

| UL | E29179 |
|----|--------|
|----|--------|

# Physical

| Circuits (maximum)       | 4          |
|--------------------------|------------|
| Color - Resin            | Natural    |
| Flammability             | 94V-0      |
| Gender                   | Receptacle |
| Glow-Wire Capable        | No         |
| Lock to Mating Part      | Yes        |
| Material - Resin         | Nylon      |
| Net Weight               | 224.900/mg |
| Number of Rows           | 1          |
| Packaging Type           | Bag        |
| Panel Mount              | No         |
| Pitch - Mating Interface | 2.50mm     |

| Polarized to Mating Part      | Yes            |
|-------------------------------|----------------|
| Stackable                     | No             |
| Temperature Range - Operating | -55° to +105°C |

## Mates With / Use With

# Mates with Part(s)

| Description                                 | Part Number |
|---|-------------|
| Mini-SPOX Vertical Single Row<br>Headers    | <u>5267</u> |
| Mini-SPOX Right-Angle Single Row<br>Headers | <u>5268</u> |

# Use with Part(s)

| Description                      | Part Number |
|----------------------------------|-------------|
| Mini-SPOX Female Crimp Terminals | <u>5263</u> |

This document was generated on Sep 15, 2024