

#### DEUTSCH | DEUTSCH DT, DEUTSCH DTM

TE Internal #: DTM04-12PC

Housing for Male Terminals, Wire-to-Wire, 12 Position, 4.19 mm [. 165 in] Centerline, Sealable, Green, Wire & Cable, Power, Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTM Housings











Connector System: Wire-to-Wire

Number of Positions: 12

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 4.19 mm [ .165 in ]

Sealable: Yes

All DEUTSCH DTM Housings (113)

## Features

## Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Blank Cavity Position	0
Number of Positions	12
Number of Rows	2
Electrical Characteristics	
Operating Voltage	250 VAC



## **Body Features**

Cable Exit Angle	180°
Primary Product Color	Green
Connector & Keying Code	С

#### **Contact Features**

Contact Size	Size 20
Contact Type	Pin
Mating Pin Diameter	1 mm[.04 in]
Contact Current Rating (Max)	7.5 A

#### Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

## **Housing Features**

Housing Material	Plastic
Centerline (Pitch)	4.19 mm[.165 in]

## Dimensions

Connector Height	43.7 mm[1.72 in]
Product Width	20.2 mm[.795 in]
Product Length	40 mm[1.57 in]
Row-to-Row Spacing	7.11 mm[.279 in]
Compatible Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]

## **Usage Conditions**

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

## Operation/Application

Circuit Application	Power

## **Industry Standards**

Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030



UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)  Candidate List Declared Against: JUNE 2024 (241)  SVHC > Threshold:  Octamethylcyclotetrasiloxane (D4) (.5% in Component Part)  Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part)  Decamethylcyclopentasiloxane (D5) (.5% in Component Part)  Article Safe Usage Statements:  Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts



TE Part # 1028-034-1205 BKSHL, 12P, BLK, REC, ST, NW 13/17



TE Part # CAT-D485-CH8172
DEUTSCH DTM Housings



TE Part # 1011-054-1205 SEAL RET, 12P, GRN, DTM, C



TE Part # CAT-D485-W416
DEUTSCH DTM Wedgelocks



TE Part # CAT-D487-M8649
DEUTSCH DT Mounting Clips



TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts



TE Part # 1924487-2 MOUNTING CLIP, AMPSEAL 16



TE Part # DT-RT1
EXT TOOL, FRONT RELEASE



TE Part # 1060-20-0144 PIN, SF, SIZE 20, 16-22, AU/SN



TE Part # 1060-20-0244 PIN, SF, SIZE 20, 16-22, AU/SN



TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # DTM12P-DC
PROTECT CVR, 12P, REC, GRY, DTM



TE Part # 1060-20-0622 PIN, SF, SIZE 20, 14-16, NI/NI



TE Part # 1060-20-0222 PIN, SF, SIZE 20, 16-22, NI/NI



TE Part # 1060-20-0122 PIN, SF, SIZE 20, 16-22, NI/NI



TE Part # 1060-20-0177 PIN, SF, SIZE 20, 16-22, SN/SN



TE Part # 1060-20-0277 PIN, SF, SIZE 20, 16-22, SN/SN



TE Part # DTM12P-BT BOOT, 12P, REC, ST, GRY



TE Part # DTM12P-BT-BK BOOT, 12P, REC, ST, BLK


TE Part # CAT-D48-SFT273
DEUTSCH Stamped and Formed
Contacts

Also in the Series | DEUTSCH DT





Automotive Connector Caps & Covers (19)



Automotive Connector Locks & Position Assurance(87)



Automotive Housings(706)



Connector Backshells(61)



Connector Seals & Cavity Plugs(6)




Connector Strain Relief(28)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(28)



PCB Headers & Receptacles(106)

# Also in the Series | DEUTSCH DTM



Automotive Connector Caps & Covers (7)



Automotive Connector Locks & Position Assurance(25)



Automotive Housings(104)





Connector Strain Relief(28)



Insertion & Extraction Tools(2)



PCB Headers & Receptacles(38)



# Customers Also Bought



TE Part #DTM04-12PB DEUTSCH DTM Housings



TE Part #WM-12P WEDGE LOCK, 12P, REC, ORG, DTM



TE Part #DTM04-08PC REC, 8P, GRN, N, C





TE Part #1060-20-0122 PIN, SF, SIZE 20, 16-22, NI/NI



Relay 26-57-08



TE Part #HC5840D INTEGRAL BATT. POST. DOUBLE TAPER.



70MM2 BATTTERY CLMP ASSMB **NEGATIVE** 



#### **Documents**

**Product Drawings** 

REC, 12P, GRN, N, C

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-12PC\_99\_c-dtm04-12pc-99.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-12PC\_99\_c-dtm04-12pc-99.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-12PC\_99\_c-dtm04-12pc-99.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Male Terminals, Wire-to-Wire, 12 Position, 4.19 mm [.165 in] Centerline, Sealable, Green, Wire & Cable, Power, Hybrid



## Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

**CONNECTOR SELECTOR** 

English

**Product Specifications** 

**Application Specification** 

English

Agency Approvals

**UL Report** 

English