




Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 5180 – 13100 CMA

Stud Size: 5/16, M8

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	5/16, M8
Sealable	No

Wire Insulation Support Retention Type	Non-Insulation Support
--	------------------------

Configuration Features

Number of Holes	1
-----------------	---

Body Features

Product Weight	1.738 g
----------------	---------

Contact Features

Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Wire Size	5180 – 13100 CMA
Stud Diameter	8.3 mm[.327 in]
Tongue Thickness	1.02 mm[.04 in]
Product Length	21.97 mm[.86 in]
Barrel Inside Diameter	3.28 mm[.129 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No
-------------------------------	----

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these




limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

<p>TE Part # 58545-1 SOLISTRAND 10-22 DIE ASSY</p>	<p>TE Part # 58546-1 PC 22-10 SOLISSPICE SPL I SHT</p>	<p>TE Part # 49935 DAHT SOLIS 22-10 ASSY</p>	<p>TE Part # 525693 DAHT SOLIS 22-10 ASSY</p>
<p>TE Part # 58545-3 SDE DIE ASSY. 22-10 SOLISTRAND</p>	<p>TE Part # 47814 DIES SOLIS 12-10 DIE SET</p>	<p>TE Part # 169400 CERTI-LOK FRAME W/O DIES</p>	

Customers Also Bought

<p>TE Part #6-146252-3 26 MODII HDR DRST B/A .100 LF</p>	<p>TE Part #350787-1 02P UMNL PIN HDR ASSY 94VO</p>	<p>TE Part #35772 TERMINAL,SOLIS R 12-10 1/4</p>	<p>TE Part #735159 250 PIDG FF</p>
<p>TE Part #63650-1 250 FASTON TAB TPBR</p>	<p>TE Part #5-103946-1 8X2 MTE SHRD PIN SR POL .100CL</p>	<p>TE Part #6-1414989-1 V23134Z1020-EV-CBOX</p>	<p>TE Part #640503-1 15P MR HDR ASSY V0</p>



Documents

Product Drawings

TERMINAL,SOLIS R 12-10 5/16

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_35773_K.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_35773_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_35773_K.3d_stp.zip

English

Customer View Model

ENG_CVM_35773_D.3d_igs.zip

English

Customer View Model

ENG_CVM_35773_D.3d_stp.zip

English

Customer View Model

ENG_CVM_35773_D.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Agency Approvals

UL Report

English

UL Report

English

35773

Closed Ring Tongue Terminal, 12 – 10 AWG, 5/16 / M8 Stud Size, 8.3 mm [.327 in]
Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated

