



### General Description


- Low  $R_{DS(on)}$  & FOM
- Extremely low switching loss
- Excellent stability and uniformity
- Fast switching and soft recovery

### Applications

- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply

### Product Summary

$V_{DS}$	100	V
$R_{DS(on),Typ} @ V_{GS}=10V$	14	m $\Omega$
$I_D$	45	A



### Absolute Maximum Ratings ( $T_A=25^{\circ}C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-source Voltage	$V_{DS}$	100	V
Gate-source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current	$I_D$	$T_C=25^{\circ}C$	45
		$T_C=100^{\circ}C$	28.5
Pulsed Drain Current <sup>A</sup>	$I_{DM}$	180	A
Avalanche energy <sup>B</sup>	$E_{AS}$	81	mJ
Total Power Dissipation <sup>C</sup>	$P_D$	$T_C=25^{\circ}C$	72
		$T_C=100^{\circ}C$	28.8
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55~+150	$^{\circ}C$

### Thermal resistance

Parameter	Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient <sup>D</sup>	$R_{\theta JA}$	$t \leq 10S$	15	$^{\circ}C/W$
Thermal Resistance Junction-to-Ambient <sup>D</sup>		Steady-State	40	
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	Steady-State	1.35	

**Electrical Characteristics** ( $T_j=25^\circ\text{C}$  unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
<b>Static Parameter</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	100			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100V, V_{GS}=0V$			1	$\mu A$
Gate-Body Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20V, V_{DS}=0V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1	1.8	3	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=20A$		14	17	m $\Omega$
		$V_{GS}=4.5V, I_D=20A$		17	21.5	m $\Omega$
Diode Forward Voltage	$V_{SD}$	$I_S=20A, V_{GS}=0V$			1.3	V
Maximum Body-Diode Continuous Current	$I_S$				45	A
Gate resistance	$R_G$	f= 1 MHz, Open drain		1		$\Omega$
<b>Dynamic Parameters</b>						
Input Capacitance	$C_{iss}$	$V_{DS}=50V, V_{GS}=0V, f=1MHz$		1135		pF
Output Capacitance	$C_{oss}$			399		
Reverse Transfer Capacitance	$C_{rss}$			18		
<b>Switching Parameters</b>						
Total Gate Charge	$Q_g$	$V_{GS}=10V, V_{DS}=50V, I_D=25A$		16		nC
Gate-Source Charge	$Q_{gs}$			5.6		
Gate-Drain Charge	$Q_{gd}$			2.4		
Reverse Recovery Charge	$Q_{rr}$	$I_F=20A, di/dt=100A/\mu s$		42		ns
Reverse Recovery Time	$t_{rr}$			39.8		
Turn-on Delay Time	$t_{D(on)}$	$V_{GS}=10V, V_{DD}=50V, I_D=25A$ $R_{GEN}=2.2\Omega$		39.2		ns
Turn-on Rise Time	$t_r$			11		
Turn-off Delay Time	$t_{D(off)}$			53.2		
Turn-off fall Time	$t_f$			15.8		

A. Repetitive rating; pulse width limited by max. junction temperature.

B.  $V_{DD}=50V, R_G=25\Omega, L=0.5mH, I_{AS}=25A$ .

C. Pd is based on max. junction temperature, using junction-case thermal resistance.

D. The value of RqJA is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation PDSM is based on R qJA  $\leq 10s$  and the maximum allowed junction temperature of  $150^\circ\text{C}$ . The value in any given application depends on the user's specific board design.



### Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. : On-Resistance vs. Drain Current and Gate Voltage




Figure6. Normalized On-Resistance




Figure7. Drain current




Figure8.Safe Operation Area





Figure9.Normalized Maximum Transient thermal impedance





### Ordering and Marking Information

Ordering Device No.	Marking	Package	Packing	Quantity
ASDM100R160NKQ-R	100R160N	TO-252	Tape&Reel	2500/Reel

PACKAGE	MARKING
TO-252	 <p>The diagram shows a rectangular marking area on a TO-252 package. It contains the following elements from top to bottom: the logo 'AS', a three-digit box labeled 'Lot Number', the part number '100R160N', and a four-digit box labeled 'Date Code'.</p>

# TO-252



**IMPORTANT NOTICE**

Xi'an Ascend Semiconductor incorporated MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Xi'an Ascend Semiconductor Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Xi'an Ascend Semiconductor Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Xi'an Ascend Semiconductor Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume .

all risks of such use and will agree to hold Ascendsemi Incorporated and all the companies whose products are represented on Xi'an Ascend Semiconductor Incorporated website, harmless against all damages.

Xi'an Ascend Semiconductor Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Xi'an Ascend Semiconductor Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Xi'an Ascend Semiconductor Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

**[www.ascendsemi.com](http://www.ascendsemi.com)**