# GA355DR7GB103KY02# "#" indicates a package specification code.


















Last Time Buy Date: 31 Mar 2019

< List of part numbers with package codes > GA355DR7GB103KY02L

### Shape



L size $5.7 \pm 0.4 \text{mm}$ W size $5.0 \pm 0.4 \text{mm}$ T size $2.0 \pm 0.3 \text{mm}$ External terminal width e $0.3 \text{mm}$ min.  Distance between external terminals g $4.0 \text{mm}$ min.  Size code in inch(mm) $2220 (5750 \text{M})$	L W	
T size 2.0 ±0.3mm  External terminal width e 0.3mm min.  Distance between external terminals g 4.0mm min.	L size	5.7 ±0.4mm
External terminal width e 0.3mm min.  Distance between external terminals g 4.0mm min.	W size	5.0 ±0.4mm
Distance between external terminals g 4.0mm min.	T size	2.0 ±0.3mm
	External terminal width e	0.3mm min.
Size code in inch(mm) 2220 (5750M)	Distance between external terminals g	4.0mm min.
	Size code in inch(mm)	2220 (5750M)

#### **Notes**

Please use alternative.



#### References

Packaging	Specifications	Minimum quantity
L	φ180mm Embossed taping	1000

Mass (typ.)	
1 piece	290.0mg
φ180mm Reel	347g

## **Specifications**

Capacitance	10000pF ±10%
Rated voltage	250Vac(r.m.s.)
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

1 of 1



<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications.