


## SOD-123

## 500mW SOD-123 Fast Switching Diode

### 特征 Features



- 开关速度小于 4.0nS; Fast Switching Device (TRR <4.0 nS)
- 最大功率耗散 500mW; Power Dissipation of 500mW
- 高稳定性和可靠性。High Stability and High Reliability
- 反向漏电流小。Low reverse leakage

### 机械数据 Mechanical Data

- 封装: SOD-123 封装 SOD-123 Small Outline Plastic Package
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 环氧树脂 UL 易燃等级 Epoxy UL: 94V-0
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性( $T_A = 25^\circ\text{C}$  除非另有规定)

**Maximum Ratings & Thermal Characteristics** (Ratings at  $25^\circ\text{C}$  ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
反向峰值电压 Peak Reverse Voltage	$V_{RM}$	100	V
功率消耗 Power Dissipation	$P_d$	500	mW
工作结温 Operating junction temperature	$T_j$	150	$^\circ\text{C}$
存储温度 Storage temperature range	$T_{STG}$	-65~+150	$^\circ\text{C}$
热阻 Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	250	$^\circ\text{C}/\text{W}$
平均整流电流 Average Rectified Current	$I_o$	150	mA
正向(不重复)电流 Non-repetitive Peak Forward Current	$I_{FM}$	300	mA
正向(不重复)浪涌电流 Peak Forward Surge Current @ $t_p=1\mu\text{s}; TA=25^\circ\text{C}$	$I_{FSM}$	2.0	A


Valid provided that electrodes are kept at ambient temperature.

**电特性 Electrical Characteristics** (Ratings at  $25^\circ\text{C}$  ambient temperature unless otherwise specified).


符号 Symbols	参数 Parameter	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
$B_v$	反向击穿电压 Breakdown Voltage	$IR=100\mu\text{A}$	100		V
$I_R$	反向漏电流 Reverse Leakage Current	$VR=20\text{V}$	---	25	nA
		$VR=20\text{V} T_j=150^\circ\text{C}$	---	50	$\mu\text{A}$
		$VR=75$	---	5	$\mu\text{A}$
$V_F$	正向电压 Forward Voltage	$IF=10\text{mA}$	---	1.00	V
		$IF=100\text{mA}$	---	1.25	
$TRR$	反向恢复时间 Reverse Recovery Time	$IF = IR = 10\text{mA},$	---	4	nS
		$Ir=0.1\times IR$			
		$RL=100\Omega$			
$C$	结电容 Capacitance	$VR=0\text{V}, f=1\text{MHz}$	---	4	pF

# 1N4148W


Forward characteristics




Admissible power dissipation versus ambient temperature




Leakage current versus junction temperature



Reverse capacitance VS. reverse voltage




Admissible repetitive peak forward current VS. pulse duration




# 1N4148W

Plastic surface mounted package




SYMBOL	DIMENSIONS	
	MIN.	MAX.
A	1.050	1.250
A1	0.000	0.100
A2	1.050	1.150
b	0.450	0.650
c	0.080	0.150
D	1.500	1.700
E	2.600	2.800
E1	3.550	3.850
L	0.500REF	
L1	0.250	0.450
θ	0°	8°



## 焊盘设计参考

Precautions: PCB Design

Recommended land dimensions for SOD-123 diode. Electrode patterns for PCBs



### 技术要求:

- 中心距: 3.24      1, 塑封体尺寸: 2.70 X 1.60
- 脚 宽: 0.55      2: 未注公差为: ±0.05
- 焊盘宽: 1.00      3, 所有单位: mm
- 脚 长: 0.50
- 焊盘长: 0.80