

COMPACT FOOTSWITCH



Compact Footswitch

[Request A Quote](#)

Environmental Ratings:

EN 60529 Degree of Protection IP20

Key Benefits

This foot switch is compact in size and light in weight. Built for long life, the strong steel housing is painted black with nonskid base pad.

Size: 2-7/8" x 2-1/2" x 1-1/8"
Weight: 7 oz.

The TWIN 491-S foot switch consists of two single models mounted on a single cast aluminum base with a divider bar between pedals which helps prevent accidental operation of both pedals at one time.

Size: 6" x 2-7/8" x 1-7/16"
Weight: 1-1/4 lbs.

SPECIFICATIONS

(Special variations are available to the O.E.M. on special order on the models listed below)

⚠ WARNING

	CATALOG NUMBER	DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
	491-S	Momentary	SPDT	C	10 A 125-250 VAC 1/2 H.P. 125-250 VAC
	491-DA	Maintained	SPST	A	10 A 125 VAC
	491-DC3A*	Maintained	SPST	A	7 A 125 VAC
	491-SC3**	Momentary	SPDT Wired N.O.	A	10 A 125 VAC 1/2 H.P. 125 VAC
	491-SC36*** 491-SC36MP***	Momentary	SPDT Wired N.O.	A	10 A 125-250 VAC 1/2 H.P. 125-250 VAC
	TWIN 491-S	Momentary	Each Side SPDT	C	10 A 125-250 VAC 1/2 H.P. 125-250 VAC
	491-DC36A****	Maintained	SPST	A	10 A 125-250 VAC 1/2 H.P. 125-250 VAC
	492-S	Momentary	SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC

*Supplied with 6 ft. 18/3 cord and 3 prong series plug. Green lead grounded.
 **Supplied with 8 ft. 16/3 cord with 3 prong series plug. Green lead grounded.
 ***Supplied with 6 ft. 16/3 cord without plug. Green lead grounded.
 ****Supplied with 6 ft. 18/3 cord without plug(Green Lead Grounded)
BOLD COPY INDICATES STOCK ITEM