



■ 技术参数 SPECIFICATIONS

- ◆ 适用线规：AWG#28~#32
- ◆ Applicable Wire: AWG#28~#32
- ◆ 额定电压：125V DC,AC(rms)
- ◆ Rated voltage: 125V DC,AC(rms)
- ◆ 额定电流：1A
- ◆ Rated Current: 1A
- ◆ 耐压值：500V AC/minute
- ◆ Withstand voltage: 500V AC/min.
- ◆ 工作温度：-25°C ~ +85°C
- ◆ Working Temp：-25°C ~ +85°C
- ◆ 绝缘电阻：≥ 1000 MΩ
- ◆ Insulation resistance: ≥ 1000 MΩ
- ◆ 接触电阻：≤ 20mΩ
- ◆ Contact resistance: ≤ 20mΩ

DIM. Poles	DIM. A	DIM. B	DIM. C
2	4.25	3.05	1.25
3	5.50	4.30	2.50
4	6.75	5.55	3.75
5	8.00	6.80	5.00
6	9.25	8.05	6.25
7	10.50	9.30	7.50

DIM. Poles	DIM. A	DIM. B	DIM. C
8	11.75	10.55	8.75
9	13.00	11.80	10.00
10	14.25	13.05	11.25
11	15.50	14.30	12.50
12	16.75	15.55	13.75
13	18.00	16.80	15.00

DIM. Poles	DIM. A	DIM. B	DIM. C
14	19.25	18.05	16.25
15	20.50	19.30	17.50
16	21.75	20.55	18.75

P.C.B Layout

②	PIN	—	Phosphor bronze	Ag-PLATED		
①	Base	—	PA46	Thermoplastic		
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	ELECTRONICS CO.,LTD	
DRAWN		JUANKUN.LU	2015.03.17	
CHECKED		TITLE: Bar Connector Series		
APPROVALS		PART NO.		1.25T-nP-DP

TOLERANCES ARE		30~以上 ±0.30	10~30 ±0.20	ANGLE	±2°	DRAWING NO.	PROJ. SHEET 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	
	A		NEW				