


- Typical Specifications :
1. Rating : DC 12V 50mA
 2. Life:300,000 Cycles Min.
 3. Travel:0.15±0.05mm



Circuit Diagram

NO.1	
PART NO	vigor
1	90±30
2	130±30
3	180±30
4	250±30
5	350±50

NO.2-NO.3	
PART NO	NOTE
01~99	SERIAL NUMBER

⑤	Knob	—	1	PET	Black	—
④	Dust cover	—	1	KAPTON FILM	Yellow	—
③	Terminal	—	4	Phosphor Bronze	Plating silver	—
②	Contact	—	2	F.Ag/SUS	Plating silver	—
①	Base	—	1	Nylon	Black	—

APPROVALS		DATE	
DRAWN	J.X.Zhang	DATE	2013/8/08

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	B					
	A		NEW			

APPROVALS		DATE	
CHECKED		DATE	2013/8/08

TOLERANCES ARE		ANGLE	
30~12.5	±0.30	30°	±2°
10~30	±0.20		
5~10	±0.15		
~5	±0.10		

PART NO.		TITLE:	
K2-1828UQ-CDDW-□□		TACT SWITCHS	

ELECTRONICS CO.,LTD	
SCALE: 1:1	PROJ.:
DRAWING NO.	SHEET 1 OF 1