



- Typical Specifications :
1. Rating : DC 12V 50mA
  2. Insulation resistance:  $\geq 100M\Omega$
  3. Withstand voltage: AC 500V/1min
  4. Life: 100,000 Cycles Min.



Circuit Diagram

NO.1	
PART NO	H
D	3.5
F	5

NO.2	
PART NO	vigor
3	180±30
4	250±30
5	350±50

NO.3-NO.4	
PART NO	NOTE
01~99	SERIAL NUMBER

⑤	Terminal	—	4	Phosphor Bronze	Plating silver	—
④	Contact	—	1	F.Ag/SUS	—	—
③	Base	—	1	PA46	Black	—
②	Cover	—	1	SPCC	Plating Sn	—
①	Keystroke	—	1	Silica gel	White	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE				
DRAWN		xu qi feng	2014.10.28			

**HONG**  
ELECTRONICS CO.,LTD

CHECKED  
APPROVALS  
TOLERANCES ARE

TITLE:	PART NO.	SCALE:	PROJ:
TACT SWITCHS	K2-1156SP-□□□□-□□	1:1	□□□□
CHECKED	30~0.1	±2°	DRAWING NO.
APPROVALS	10~0.30	±2°	
TOLERANCES ARE	5~0.10	±2°	
	~5	±2°	SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	B		修改按耐材质为蓝色硅胶20180407			
	A		修改型号为单弹20160927 NEW			