


# isc Silicon NPN Darlington Power Transistor

2N6355

## DESCRIPTION

- High DC current gain  
:  $h_{FE} = 500(\text{Min}) @ I_C = 4A$
- With TO-3 package
- Low collector saturation
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation




## APPLICATIONS

- Designed for general-purpose power amplifier and low -frequency swithing applications.

## ABSOLUTE MAXIMUM RATINGS( $T_a = 25^\circ C$ )

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	50	V
$V_{CEO}$	Collector-Emitter Voltage	40	V
$V_{EBO}$	Emitter-Base Voltage	5	V
$I_C$	Collector Current-Continuous	20	A
$I_B$	Base Current-Continuous	0.5	A
$P_C$	Collector Power Dissipation@ $T_c = 25^\circ C$	150	W
$T_J$	Junction Temperature	200	$^\circ C$
$T_{stg}$	Storage Temperature	-65~200	$^\circ C$



## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th j-c}$	Thermal Resistance, Junction to Case	1.09	$^\circ C/W$

## isc Silicon NPN Darlington Power Transistor

2N6355

## ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$V_{CEQ(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=50\text{mA}; I_B=0$	40			V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=10\text{A}; I_B=40\text{mA}$			2.0	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=20\text{A}; I_B=1\text{A}$			4.0	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=20\text{A}; I_B=1\text{A}$			4.0	V
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C=10\text{A}; V_{CE}=4\text{V}$			2.8	V
$I_{EBO}$	Emitter Cutoff Current	$V_{EB}=5\text{V}; I_C=0$			5	mA
$I_{CEO}$	Collector Cutoff Current	$V_{CE}=40\text{V}; I_B=0$			1	mA
$I_{CBO}$	Collector Base Cutoff Current	$V_{CB}=50\text{V}; I_E=0$			0.5	mA
$h_{FE-1}$	DC Current Gain	$I_C=4\text{A}; V_{CE}=5\text{V}$	500		5000	
$h_{FE-2}$	DC Current Gain	$I_C=20\text{A}; V_{CE}=5\text{V}$	100			

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.