


Code-x	H	Code-x	H
A	4.3	O	11.0
B	4.5	P	11.5
C	5.0	Q	12
D	5.5	R	12.5
E	6.0	S	13.0
F	6.5	T	13.5
G	7.0	U	14.0
H	7.5	V	15.0
I	8.0	W	15.5
J	8.5	X	16
K	9.0	Y	16.5
L	9.5	Z	17
M	10.0		
N	10.5		

SPECIFICATION
 Contact rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Dielectric Strength: 250V AC/1minute
 Travel: 0.25mm
 Operating Temp: -30 °C ~ + 85 °C
 Storage Temp: -30 °C ~ + 80 °C



PAPT NO	TC-1102DE-X-X
Operating Force	A:100gf B:160gf C:260gf
Height	Code-x

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	---	3	Brass (0.30t)	ag Plated	---
④	Contact	---	1	F.ag/SUS	---	---
③	Base	---	1	PPA	---	---
②	Cover	---	1	Brass	Tin plated	---
①	Keystake	---	1	PPA	---	---

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δx				
△x				
⊗x				

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGULAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5



DSND		SCALE: N/A
DWN		VIEW:
CHKD		UNIT: mm/in
APPD		SIZE: A4

MODEL TYPE:	TACT SWITCH	
PART NO.:	TC-1102DE-X-X	
DWG NO.:		
WEIGHT	SHEET	REVISIC
	1/1	A0

XKB INDUSTRIAL PRECISION CO., LIMITED