


FEATURES

- M3 x 5mm screw terminals
- Wire protection leaf
- Nylon 6.6 housing with nickel plated brass clamps

RS PRO, 12 Way, 4mm², Nylon Non-Fused Terminal Block, 400V

RS Stock No.: 464-9722



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

From RS PRO, this non-fused terminal block presents a reliable and cost-effective solution to wire-to-wire connections. The terminal block is direct-mount and so does not require the use of a DIN Rail to mount. Instead, it features two mounting screws that allow mounting to any surface. This nylon terminal block can easily be cut to a required length, allowing for a highly customizable connector solution.

General Specifications

Fused	No
Mounting Type	Through Hole
Contact Material	Brass
Termination Method	Screw Down
Contact Plating	Nickel
Colour	Natural
Material	Nylon 66
Number of Ways	12
Applications	Connecting lighting to switches, Connecting wiring to a ground, HVAC Systems, Power Supplies

Electrical Specifications

Current Rating	41A
Voltage Rating	400V

Mechanical Specifications

Wire Size	4mm ²
Pitch	12mm
Screw Size	M4 x 7

Operation Environment Specifications

Maximum Operating Temperature	125°C
-------------------------------	-------

Approvals

Standards Met	RoHS, CE, UL 94V-2, IEC 695-2-1, 2
---------------	------------------------------------

