



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 50V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: Wafer Nylon 6T, UL94V-0
PIN Phosphoric bronze Tin-plated
Solder tad Phosphoric bronze Tin-plated

编 号	尺寸 (mm)	
	A	B
A1001LF-2X06A	5.00	8.30
A1001LF-2X08A	7.00	10.30
A1001LF-2X10A	9.00	12.30
A1001LF-2X15A	14.00	17.30
A1001LF-2X20A	19.00	22.30
A1001LF-2X25A	24.00	27.30



X. ±0.5	X* ±
.X ±0.30	X* ±
.XX ±0.20	.XX* ±
.XXX ±0.005	.XXX* ±

单位 UNIT	mm	深圳市泰华电子有限公司 TaiHua Electronics Co., Ltd
比例 SCALE		
核准: APPROVED BY	版本: A0	产品名称 Product Name
审核: CHECKED BY	页次: 1/1	1.0双排立贴 WAFER SMT TYPE
制图: DRAWN BY	日期: DATE	产品料号 Product No
	2022.8.31	TH-A1001LF-2XNA
		客户料号 Client No

版本 REV	变更日期 CHANGE DATE	变更理由 CHANGE REASON
A0		