



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2506-02AWD	2.50	7.50
A2506-03AWD	5.00	10.00
A2506-04AWD	7.50	12.50
A2506-05AWD	10.00	15.00
A2506-06AWD	12.50	17.50
A2506-07AWD	15.00	20.00
A2506-08AWD	17.50	22.50
A2506-09AWD	20.00	25.00
A2506-10AWD	22.50	27.50
A2506-11AWD	25.00	30.00
A2506-12AWD	27.50	32.50
A2506-20AWD	47.50	52.50



单位
UNIT

比例
SCALE

核准:
APPROVED BY

审核:
CHECKED BY

制图:
DRAWN BY

泰华电子有限公司
TaiHua Electronics Co., Ltd

版本: A0
产品名称: 52064定位弯针 WAFER DIP TYPE

页次: 1/1
产品料号: TH-A2506-NAWD

日期: 客户料号

制图: 2022.3.1
客户料号

版本 REV	变更事项 CHANGE CONTENT	依据 REFERENCE	变更日期 DATE
A0			