


PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2506-02A	2.50	7.50
A2506-03A	5.00	10.00
A2506-04A	7.50	12.50
A2506-05A	10.00	15.00
A2506-06A	12.50	17.50
A2506-07A	15.00	20.00
A2506-08A	17.50	22.50
A2506-09A	20.00	25.00
A2506-10A	22.50	27.50
A2506-11A	25.00	30.00
A2506-12A	27.50	32.50
A2506-20A	47.50	52.50



单位 UNIT	mm	泰华电子有限公司 <i>TaiHua Electronics Co., Ltd</i>	
比例 SCALE	1:1		
核准: APPROVED BY	XX ±	版本: VERSION	A0
检查: CHECKED BY	.XX ±	页次: PAGE	1/1
日期: DATE	.XXX ± 0.005, .XXX ±	制图: DRAWN BY	封文馨 2022.3.1
		产品名称 Production name	5264直针 WATER DIP TYPE
		产品料号 Product No	TH-A2506-NA
		客户料号 Client No	