



PCB LAYOUT

编号	尺寸 (mm)	
	A	B
A4250-2X01AW	5.40	5.40
A4250-2X02AW	4.20	9.60
A4250-2X03AW	8.40	13.80
A4250-2X04AW	12.60	18.00
A4250-2X05AW	16.80	22.20
A4250-2X06AW	21.00	26.40
A4250-2X07AW	25.20	30.60
A4250-2X08AW	29.40	34.80
A4250-2X09AW	33.60	39.00
A4250-2X10AW	37.80	43.20
A4250-2X11AW	42.00	47.40
A4250-2X12AW	46.20	51.60

- SPECIFICATIONS
- Current Rating: 9A AC, DC
 - Voltage Rating: 600V AC, DC
 - Temperature Range: -25°C~+85°C
 - Contact Resistance: 20mΩ Max
 - Insulation Resistance: 1000MΩ Min
 - Withstanding Voltage: 1500V AC/minute
 - Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated



X. ±0.5 X*±
X. ±0.30 X*±
. XX ±0.20 . XX*±
. XXX ±0.005 . XXX*±

单位 UNIT	mm
比例 SCALE	
核准: APPROVED BY	版本: A0
审核: CHECKED BY	页次: 1/1
制图: DRAWN BY	日期:
	封文辉 2022.12.05
	客户料号 Client No

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

5569 双排弯针
WATER DIP TYPE

产品名称
Production name

TH-A4250-2X12AW