



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 15A AC, DC
  - 2、Voltage Rating: 600V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 5000V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
G6350-3X02A	6.35	14.20
G6350-3X03A	12.70	20.55
G6350-3X04A	19.05	26.90
G6350-3X05A	25.40	33.25

深圳市泰华电子有限公司  
**TaiHua Electronics Co., Ltd**

	X.±0.5	X*±	单位	mm
	.X±0.30	.X*±	UNIT	
.XX±0.20	.XX*±	比例		
.XXX±0.008, XXX*±		SCALE		
核准:	APPROVED BY	版本:	A0	产品名称
审核:	CHECKED BY	页次:	1/1	Production name
制图:	DRAWN BY	日期:		63080三排直针 WAFER DIP TYPE
				产品料号
				Product No
				客户料号
				Client No

版本	变更日期	变更日期
A0	DATE: 2023.01.31	DATE: