


PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 800V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)		
	A	B	C
A2009-2x02A	2.00	6.00	3.00
A2009-2x03A	4.00	8.00	3.00
A2009-2x04A	6.00	10.00	3.00
A2009-2x05A	8.00	12.00	5.00
A2009-2x06A	10.00	14.00	7.00
A2009-2x07A	12.00	16.00	9.00
A2009-2x08A	14.00	18.00	11.00
A2009-2x09A	16.00	20.00	13.00
A2009-2x10A	18.00	22.00	15.00
A2009-2x11A	20.00	24.00	17.00
A2009-2x12A	22.00	26.00	19.00
A2009-2x13A	24.00	28.00	21.00
A2009-2x14A	26.00	30.00	23.00
A2009-2x22A	42.00	46.00	39.00



单位 UNIT mm

比例 SCALE

公差: .x.±0.5
x.±
.x±0.30
x.±
.xx±0.20
.xx.±
.xxx±0.003, .xxx.±

批准: APPROVED BY
审核: CHECKED BY
制图: DRAWN BY

版本: A0
页次: 1/1
日期:

产品名称 Production name
产品料号 Product No
客户料号 Client No

泰华电子有限公司
TaiHua Electronics Co., Ltd

PHB直针 WAFER DIP TYPE

TH-A2009-NA

封文辉
2022.9.5

日期:

客户料号
Client No