



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 - 4、Contact Resistance: $20\text{m}\Omega$ Max
 - 5、Insulation Resistance: $1000\text{M}\Omega$ Min
 - 6、Withstanding Voltage: 800V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2023-2X02A	2.00	6.00
A2023-2X03A	4.00	8.00
A2023-2X04A	6.00	10.00
A2023-2X05A	8.00	12.00
A2023-2X06A	10.00	14.00
A2023-2X07A	12.00	16.00
A2023-2X08A	14.00	18.00
A2023-2X09A	16.00	20.00
A2023-2X10A	18.00	22.00
A2023-2X11A	20.00	24.00
A2023-2X12A	22.00	26.00
A2023-2X22A	42.00	46.00

		<p>泰华电子有限公司 TaiHua Electronics Co., Ltd</p>	
单位 UNIT	mm	版本: A0	产品名称 PHDC带钩直针 WAFER DIP TYPE
比例 SCALE		页次: 1/1	产品料号 TH-A2023-2XNA
核准: APPROVED BY		日期:	客户料号 Client No
审核: CHECKED BY			
制图: DRAWN BY	封文辉 2022.9.5		