



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000 MΩ Min
- 6、Withstanding Voltage: 800V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0

PIN Brass Tin-plated
Solder foot Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2008-2X07AW	12.00	22.00
A2008-2X08AW	14.00	24.00
A2008-2X09AW	16.00	26.00
A2008-2X10AW	18.00	28.00
A2008-2X11AW	20.00	30.00
A2008-2X12AW	22.00	32.00
A2008-2X13AW	24.00	34.00
A2008-2X14AW	26.00	36.00

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

	单位	mm
$x \pm 0.5$	比例	SCALE
$x \pm 0.30$	核准:	APPROVED BY
$.xx \pm 0.20$	审核:	CHECKED BY
$.xxx \pm 0.003, .xxx \pm$	制图:	DRAWN BY
	版本:	A0
	页次:	1/1
	日期:	
	产品名称	PHDT直针 WAFER DIP TYPE
	产品料号	TH-A2008-2X14AW
	客户料号	
	客户名称	

版本	变更日期	变更日期
1.00	01/05/2011	2011/05/01