


SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 800V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A2004-2X02Y	2.00	6.00
A2004-2X03Y	4.00	8.00
A2004-2X04Y	6.00	10.00
A2004-2X05Y	8.00	12.00
A2004-2X06Y	10.00	14.00
A2004-2X07Y	12.00	16.00
A2004-2X08Y	14.00	18.00
A2004-2X09Y	16.00	20.00
A2004-2X10Y	18.00	22.00
A2004-2X11Y	20.00	24.00
A2004-2X12Y	22.00	26.00
A2004-2X20Y	38.00	42.00



单位 UNIT mm

比例 SCALE

X. ±0.5 X* ±
 . X ±0.30 X* ±
 . XX ±0.20 . XX* ±
 . XXX ±0.005 . XXX* ±

批准: APPROVED BY
 审核: CHECKED BY
 制图: DRAWN BY

版本: A0 产品名称
 生产名称
 日期: 1/1 产品料号
 客户料号

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd
 PHD孔座
 TH-A2004-2XNV

2022.9.5 封文辉

客户料号