



- SPECIFICATIONS**
- 1、Current Rating: 2A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 800V AC/minute
 - 7、Material: Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A2001-02Y	2.00	5.80
A2001-03Y	4.00	7.80
A2001-04Y	6.00	9.80
A2001-05Y	8.00	11.80
A2001-06Y	10.00	13.80
A2001-07Y	12.00	15.80
A2001-08Y	14.00	17.80
A2001-09Y	16.00	19.80
A2001-10Y	18.00	21.80
A2001-11Y	20.00	23.80
A2001-12Y	22.00	25.80
A2001-16Y	30.00	33.80



X. ±0.5	X* ±
. X ±0.30	. X* ±
. XX ±0.20	. XX* ±
. XXX ±0.005	. XXX* ±

单位 UNIT	mm
比例 SCALE	
核准: APPROVED BY	版本: A0
审核: CHECKED BY	页次: 1/1
制图: DRAWN BY	日期:
	封文辉 2022.9.5
	客户料号 Client No

泰华电子有限公司
TaiHua Electronics Co., Ltd

PH孔座

TH-A2001-NV