



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2501-02A	2.50	7.50
A2501-03A	5.00	10.00
A2501-04A	7.50	12.50
A2501-05A	10.00	15.00
A2501-06A	12.50	17.50
A2501-07A	15.00	20.00
A2501-08A	17.50	22.50
A2501-09A	20.00	25.00
A2501-10A	22.50	27.50
A2501-11A	25.00	30.00
A2501-12A	27.50	32.50
A2501-20A	47.50	52.50



单位
UNIT

mm

比例
SCALE

x. ±0.5
x* ±

.x ±0.30
x* ±

.xx ±0.20
xx* ±

.xxx ±0.005
xxx* ±

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

批准: APPROVED BY
审核: CHECKED BY
制图: DRAWN BY

版本: A0
页次: 1/1
日期: 2022.9.6

产品名称
Production name
产品料号
Product No
客户料号
Client No

TJ03直针 WAFER DIP TYPE
TH-A2501-NA

版本 REV	变更日期 CHANGE DATE	变更内容 CHANGE CONTENT	变更人 BY
01			