


PCB LAYOUT

编号	尺寸 (mm)		
	A	B	C
A2501LF-02A	2.50	7.50	10.00
A2501LF-03A	5.00	10.00	12.50
A2501LF-04A	7.50	12.50	15.00
A2501LF-05A	10.00	15.00	17.50
A2501LF-06A	12.50	17.50	20.00
A2501LF-07A	15.00	20.00	22.50
A2501LF-08A	17.50	22.50	25.00
A2501LF-09A	20.00	25.00	27.50
A2501LF-10A	22.50	27.50	30.00
A2501LF-11A	25.00	30.00	32.50
A2501LF-12A	27.50	32.50	35.00
A2501LF-20A	47.50	52.50	55.00

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer LCP, PA6T, UL94V-0
- PIN Brass Tin-plated
Solder tad Phosphoric bronze Tin-plated



单位 UNIT mm

比例 SCALE

核准: APPROVED BY

审核: CHECKED BY

日期: DATE

封文辉

2022.9.6

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

版本: A0 产品名称: TJC3立脚 WAFER SMT TYPE

页次: 1/1 产品料号: TH-A2501LF-NA

制图: 客户料号: Client No

2022.9.6