


### SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 100V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 500MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A1500-02YA	1.50	4.50
A1500-03YA	3.00	6.00
A1500-04YA	4.50	7.50
A1500-05YA	6.00	9.00
A1500-06YA	7.50	10.50
A1500-07YA	9.00	12.00
A1500-08YA	10.50	13.50
A1500-09YA	12.00	15.00
A1500-10YA	13.50	16.50
A1500-11YA	15.00	18.00
A1500-12YA	16.50	19.50
A1500-20YA	21.00	24.00



x ±0.5 x\*±

. x±0.30 . X\*±

. xx±0.20 . xx\*±

. xxx±0.005, xxx\*±

单位  
UNIT  
mm

比例  
SCALE

核准:  
APPROVED BY

审核:  
CHECKED BY

制图:  
DRAWN BY

泰华电子有限公司  
*TaiHua Electronics Co., Ltd*

版本: A0 产品名称: ZH方孔插座

比例: 1/1

日期: 2022.9.6

客户料号: TH-A1500-NYA

客户料号: Client No

日期: 2022.9.6